

CE3ON

MODEL: CR-B807W

THERMAL PRINTER

Upgrade functions for mobility:

- a. 50mm diameter paper roll.
- b. 70mm/second print speed.
- c. Warning alarm for paper-lacking and power near off.
- d. Sleep and auto power off after 60 second of printer is no print.
- e. Support page mode, AP and STA mode.



*thermal mobile printer
without cutter, USB + Bluetooth (options of BM-iC3F, USB+WiFi, and BM-iC3T, USB+WiFi+Bluetooth)*



Technical Specifications

Model Numbers	CR-B807W
Printing method	Direct thermal
Printing speed	70mm/s
Paper width	79.5 ± 0.5mm
Paper roll diameter	50mm
Paper thickness	0.06~0.08mm
Character per line	576 dots/line 512 dots/line
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Interface	USB+Bluetooth / USB+Wifi / USB+Wifi+Bluetooth
Bar code	1D Barcode: UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODABAR/ITF/CODE39/CODE93/CODE128 2D Barcode: QR CODE/PDF417
Extended characters	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)
NV FLASH	64 K Bytes
Input buffer	32 K Bytes
Power supply	Input: AC 110V/240V, 50~60Hz
Power	Output: AC 9V-2A
Battery	2000mAh
Reliability	Printing head life: 50 km
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Operating system	Win XP/Win 7/Win 8/Win 10/Linux/IOS/Android
Gross weight	0.325 kg
Dimension	136×116×60mm (L × W × H)

CBON Tech

No. 65, Lin_gaang Road,
Sec.5, Long-Jiing Hsiang,
Taichung- Taiwan.
info@cbontech.com

Contact us for details