

## 2MP LowLight AHD Bullet Camera

# CC-HB221-DF36M



### Key Features

- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP66 waterproof and dustproof design, high reliability
- Metal Case

## Specifications

	CC-HB221-DF36M HD Camera
<b>Sensor</b>	
Pixel	2.0 megapixel
Size	1/2.9"
Min. Illumination	0.01 lux (F2.0, AGC ON) 0 lux (white light on)
<b>Lens</b>	
Lens	3.6mm@F2.0
Lens mount	M12
Angle of View (H)	86°
<b>Illuminator</b>	
Illuminator	IR
Illumination distance	30~35m
Lifetime	≥60,000 hours
<b>Video</b>	
Resolution	1920 (H) × 1080 (V)
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/10000s NTSC: 1/30s-1/10000s
<b>Image</b>	
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	N/A
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	Supports 180° horizontal flip, 180° vertical flip
<b>Audio</b>	
Microphone	N/A
<b>Interface</b>	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
<b>Operating environment</b>	
Temperature	-20°C to 55°C
Humidity	≤95% (RH, non-condensing)
Ingress protection	IP66
<b>General</b>	
Power	DC 12V (±25%), with reverse polarity protection. Max 3.12W
Material	Metal Case
Certification	CE