

## 2MP Full Color DarkHunter AHD Bullet Camera

### CC-HB221-DF36M-W



#### Key Features

- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports White light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP66 waterproof and dustproof design, high reliability
- Metal Case

## Specifications

|                              |   |
|------------------------------|---|
|                              | CC-HB221-DF36M-W HD Camera  |
| <b>Sensor</b>                |   |
| Pixel                        | 2.0 megapixel   |
| Size                         | 1/2.9"  |
| Min. Illumination            | 0.002 lux (F1.2, AGC ON)<br>0 lux (white light on)                                      |
| <b>Lens</b>                  |   |
| Lens                         | 3.6mm@F1.2  |
| Lens mount                   | M12   |
| Angle of View (H)            | 86°   |
| <b>Illuminator</b>           |   |
| Illuminator                  | Four white-light illuminators   |
| Illumination distance        | 40m   |
| Lifetime                     | ≥60,000 hours   |
| <b>Video</b>                 |   |
| Resolution                   | 1920 (H) × 1080 (V)   |
| Frame rate                   | TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC |
| Shutter time                 | PAL: 1/25s-1/10000s<br>NTSC: 1/30s-1/10000s   |
| <b>Image</b>                 |   |
| Exposure mode                | Four modes: Global (default), BLC, HLC, DWDR  |
| Day/Night                    | 24/7 color images   |
| Digital noise reduction      | 2D/3D   |
| White balance                | Two modes: Auto (default), Manual   |
| WDR                          | DWDR  |
| Flip                         | Supports 180° horizontal flip, 180° vertical flip                                       |
| <b>Audio</b>                 |   |
| Microphone                   | N/A   |
| <b>Interface</b>             |   |
| Power                        | 5.5mm power interface   |
| Video output                 | BNC, supports TVI/AHD/CVI/CVBS  |
| <b>Operating environment</b> |   |
| Temperature                  | -20°C to 55°C   |
| Humidity                     | ≤95% (RH, non-condensing)   |
| Ingress protection           | IP66  |
| <b>General</b>               |   |
| Power                        | DC 12V (±25%), with reverse polarity protection. Max 3.12W                              |
| Material                     | Metal Case  |
| Certification                | CE  |